

LC-3115A-LCR

Three-Way, Bi-Amplified, Screen Speaker System

SCREEN SYSTEMS



KEY FEATURES

- Ultra-long magnet design effectively reduces the voice coil current and distortion. This in turn improves the speaker's efficiency and power, delivering a higher SPL and a clean, powerful sound.
- Three-way design improving intelligibility of dialogue compared to a conventional two-way speaker system.
- Horn loaded Mid and tweeter section features an optimized aperture for ultra-low distortion, and extremely uniform frequency response.
- Ideally suited for placement within a baffled wall system.
- Ported reflex enclosure design delivers clean bass with minimal distortion at high SPL
- Designed for high end home cinema and small commercial applications

DESCRIPTION



The LC-3115A-LCR is a high resolution three-way bi-amplified screen speaker system. LNC's latest technical innovations are integrated into this screen speaker system. Featuring an optimized aperture waveguide, maximum power handling along with extremely low distortion. This screen system provides seamless transitions between screen speakers and is well suited for baffled wall applications.

SPECIFICATION


LC-3115A-LCR	
BASS:	1x 15" LF Drivers
MID:	2 x 6.5" MF Drivers
HORN:	1 x 3" Compression HF Driver
POWER:	500W (LF Driver) / 300w (MFHF Drivers)
SENSITIVITY (2.83v/1m):	98dB (LF Driver) / 105dB (MFHF Drivers)
IMPEDANCE:	LF: 8Ω / MF-HF: 8Ω
MAX PEAK OUTPUT:	131dB / 136dB
CROSSOVER:	350Hz (Active)
COVERAGE (HxV)	80°x45°
FREQUENCY RESPONSE:	32Hz - 20kHz (Bi-Amped)
DIMENSION (WxHxD):	780 x 1495 x 488mm
WEIGHT:	75kg

DIMENSIONS

Dimensions in mm



Frequency Response



Impedance